



# SQ3000 3D AOI

Automated Optical Inspection

[www.nordson.com/TestInspect](http://www.nordson.com/TestInspect)

**Nordson**  
TEST & INSPECTION

# Nordson TEST & INSPECTION

Founded in 1954, Nordson Corporation is a market leading industrial technology company with annual revenues of over \$2.1 billion and more than 7,500 employees worldwide.

Nordson TEST & INSPECTION offers its SMT & Semiconductor customers a robust product portfolio, including Acoustic, Optical and both Manual and Automated X-ray Inspection systems, X-ray Component Counting systems and Semiconductor measurement sensors. Nordson TEST & INSPECTION is uniquely positioned to serve its customers with best-in-class precision technologies, passionate sales and support teams, global reach, and unmatched consultative applications expertise.





Exceptional support from Nordson's worldwide network

## AOI Products

### Proprietary Advanced Technology

Optical Inspection & Metrology



## WS Products

### Improve Your Yields


Semiconductor Metrology Sensors



## AMI Products

### Qualify Your Design



Acoustic Inspection



## BT Products

### Test Your Design



Bondtesters



## AXI Products

### High Speed High Flexibility



Automated X-ray Inspection



## MXI Products

### Making the Invisible, Visible



Manual X-ray Inspection



## AXM Products

### Measuring the Invisible


Automated X-ray Metrology



## CC Products

### Maximize Efficiency



X-ray Component Counting



## XRT Products

### High Speed High Resolution

X-ray Technologies





# The Ultimate in Speed & Accuracy

# 3D AOI


The SQ3000 3D AOI solution is loaded with powerful tools that cover inspection and measurement for AOI applications.



High Precision Accuracy with Multi-Reflection Suppression® (MRS®) Sensor Technology.

## MRS Sensor Solutions for Metrology, Assembly, and Process Improvement

The SQ3000 with MRS technology has multiple sensor options to meet even the most demanding applications. Nordson TEST & INSPECTION has advanced the proprietary Multi-Reflection Suppression (MRS) sensor to an even finer resolution. The Ultra-High Resolution MRS sensor enhances the SQ3000 3D AOI platform, delivering superior inspection performance, ideally suited for the 0201 metric process and microelectronic applications where an even greater degree of accuracy and inspection reliability is critical.



Packaging SMT

## Large Board Capability

The SQ3000™ X supports large boards up to 710 x 610 mm, and is capable of inspecting the most demanding assemblies at production speed without compromising on measurement accuracy and repeatability.



**Shorter Inspection Times**



**Unmatched Accuracy and Resolution with MRS Technology**



**Versatility for Applications with High Quality Requirements**





# Multi-Reflection Suppression<sup>®</sup> (MRS<sup>®</sup>) Sensor Technology

The SQ3000 is powered by CyberOptics' breakthrough 3D sensing technology comprising four multi-view 3D sensors and a parallel projector delivering metrology grade accuracy at production speed.

## Reflection based distortions

MRS is designed to Inhibit reflection-based distortions from shiny and specular surfaces.




Nordsons' unique sensor architecture simultaneously captures and transmits multiple images in parallel while proprietary 3D fusing algorithms merge the images together. The result is ultra-high quality 3D images and high-speed inspection.

SQ3000 offers unmatched accuracy with the revolutionary MRS technology by meticulously identifying and rejecting reflections caused by shiny components and reflective solder joints.

MULTIPLE MRS SENSOR OPTIONS			
Standard MRS Sensor	High Speed	High Resolution	Ultra High Resolution

Effective suppression of multiple reflections is critical for accurate measurement making MRS an ideal technology solution for a wide range of applications including those with very high quality requirements.





# Enable Smarter, Faster Inspection

The multi-award winning SQ3000 AOI software is a more powerful yet extremely simple software suite designed with an intuitive interface and multi-touch control with 3D image visualization tools.



## Ultra-fast programming capabilities

Bring the ease-of-use to a completely new level and significantly speed setup, simplify the process, reduce training efforts and minimize operator interaction – all saving time and cost.

## Enable smarter, faster inspection


Speed programming and performance with AI<sup>2</sup> (Autonomous Image Interpretation) technology for set-up in <13 minutes with a data-rich, pre-loaded library and automated scripts that collect and update models all on their own.

Inspect the most comprehensive list of features and identify the widest variety of defects. AI<sup>2</sup> offers precise discrimination with just one panel inspection making it the perfect solution for high-mix and high-volume applications.


## AI<sup>2</sup>

AI<sup>2</sup> technology is all about keeping it simple - no parameters to adjust or algorithms to tune. you don't need to anticipate defects or pre-define variance. AI<sup>2</sup> does it all for you. Powered by a data-rich, pre-loaded library and automated scripts that collect and update models all on their own.

With AI<sup>2</sup>, you have the power to inspect the most comprehensive list of features and identify the widest variety of defects. AI<sup>2</sup> offers precise discrimination with just one panel inspection making it a perfect solution for high-mix and high volume applications.



Failed Model.



Passed Model.



# Faster, Highly Accurate CMM Suite

Nordson Software Solution provides our customers and partners the best added-value for inspection and measurement in electronics manufacturing.



## CyberCMM software suite

CyberCMM™, a comprehensive software suite of coordinate measurement tools, provides highly accurate, 100% metrology-grade measurement on all critical points much faster than a traditional CMM, including coplanarity, distance, height and datum X, Y to name a few. A fast and easy set-up can be performed with the world's first in-line CMM system for programming complex applications as compared to slow, engineering resource-intensive set-ups that typically requires multiple adjustments with traditional coordinate measurement machines (CMMs).




Measure critical points faster than traditional measurement systems.

## Fast, scalable SPC solution

CyberReport™ offers full-fledged machine to factory level SPC capability with powerful historical analysis and reporting tools. The software delivers complete traceability for effective process verification and yield improvement.

CyberReport is designed for simple set-up and intuitive use, while simultaneously delivering scalability, fast charting, and an extremely compact database size.





# High End Applications

The SQ3000 3D AOI offers unmatched accuracy with the revolutionary Multi-Reflection Suppression (MRS) technology. Effective suppression of multiple reflections is critical for accurate measurement, making MRS an ideal technology solution for a wide range of applications including those with very high quality requirements.



## Advanced Packaging



Fine pitch component inspection. BGA solder ball inspection, diameter measurement, uniformity. BGA coplanarity inspection.



## LED



Backlight. Five point & solder paste inspection. Pad Gap inspection. Warpage coplanarity, Illumination Intensity & Adhesive Squeeze out measurements. Dye chip out.




## Advanced Socket Metrology



Pin inspection, True position, Inspection on dispensed material, Inspecting dispensed patterns.




## Solder Paste



Tight area, Off water bridging, Speed and accuracy, Jet print paste, Type 4 paste.




## Semiconductor



Highly reflective dye, Wirebond, Ribbons, Ball bond, Wirebonding and wedgebond inspection, Wirebond loop height of wire bond, Cornerfill/Underfill inspection.

## SMT Electronics




Microelectronics, Fast and accurate inspection with low false calls, Fast programming, Speed and Accuracy, Quick programming.

## Medical



Tighter tolerance, Higher demand for accuracy, Small components, More micro electronics, Conformal coating, Life Critical.

## Defense



Component Verification, Counterfeit part detection, High map & Point cloud output capabilities, Adhesive & epoxy inspection.

## Aerospace



Metal modules that have cavities, Substrate & Critical inspection on highly reflective material, Wire bond and ribbon inspection.

## Automotive



Tuning forks, connector, True position for key features, True position for key component for high precision placement, Smaller Modules, Critical pin inspection

# Specifications

Inspection Capabilities	Standard MRS Sensor	High-Speed MRS Sensor	High-Resolution MRS Sensor	Ultra-High Resolution MRS Sensor
Inspection Speed	40 cm <sup>2</sup> /sec (2D+3D)	50 cm <sup>2</sup> /sec (2D+3D)	20 cm <sup>2</sup> /sec (2D+3D)	15 cm <sup>2</sup> /sec (2D+3D)
Minimum Component Size	0402 mm (01005 in.)		0201 mm (008004 in.)	
PCB Size	SQ3000: Minimum: 50 x 50 mm (2 x 2 in.); Maximum: 510 x 510 mm (20 x 20 in.) SQ3000-X: Minimum: 50 x 120 mm (2 x 4.7 in.); Maximum: 710 x 610 mm (27.9 x 24 in.)			
Component Height Clearance	Top: 50 mm ; Bottom: 30mm			
PCB Thickness	0.3 - 5 mm			
Component Types Inspected	Standard SMT (chips, J-lead, gull-wing, BGA, etc.), through-hole, odd-form, clips, connectors, header pins, and more			
Component Defects	Missing, polarity, tombstone, billboard, flipped, wrong part, gross body and lead damage, and more			
Solder Joint and Other Defects	Gold finger contamination, excess solder, insufficient solder, bridging, through-hole pins			
3D Measurement Inspection	Lifted Lead, package coplanarity, polarity dimple and chamfer identification			
Measurement Gage R&R	<10% @ ±3σ (±80 μm process tolerance)			
Z Height Accuracy	1 μm on certification target			
Z Measurement Range	6 mm at spec, 24 mm capability		3 mm at spec, 8 mm capability	

Vision System & Technology				
Imagers	Multi-3D sensors			
Resolution	Sub 10 μm		7 μm	
Field of View (FOV)	36 x 30 mm	36 x 36 mm	26 x 26 mm	21 x 21 mm
Image Processing	Autonomous Image Interpretation (AI <sup>2</sup> ) Technology, Coplanarity and Lead Measurement			
Programming Time	<13 minutes (for established libraries)			
CAD Import	Any column-separated text file with ref designator, XY, Angle, Part no info; Valor process preparation			

System Specifications	
Machine Interface	SMEMA, RS232 and Ethernet
Power Requirements	100-120 VAC or 220-240 VAC, 50/60 hz, 10-15 amps
Compressed Air Requirements	5.6 Kg/cm <sup>2</sup> to 7.0 Kg/cm <sup>2</sup> (80 to 100 psi @ 4 cfm)
System Dimensions	SQ3000: 110 x 127 x 139 cm (W x D x H) • SQ3000-X: 134 x 139 x 139 cm (W x D x H)
Weight	SQ3000: ≈965 kg (2127 lbs.) • SQ3000-X: ≈1242 kg (2738 lbs.)

Options	
	Barcode Reader, Rework station, SPC Software, Alignment Target SQ3000™ D (Dual Lane), and SQ3000™ DD (Dual Lane - Dual Sensor) models available

**For more information, speak with your Nordson representative or contact your Nordson regional office**

**Nordson Test & Inspection Europe, SEA, Africa**  
ti-sales-eu@nordson.com

**Nordson Test & Inspection Americas**  
ti-sales-us@nordson.com

**Nordson Test & Inspection China**  
ti-sales-cn@nordson.com

**Nordson Test & Inspection Japan**  
ti-sales-jp@nordson.com

**Nordson Test & Inspection Singapore**  
ti-sales-eu@nordson.com

**Nordson Test & Inspection Taiwan**  
ti-sales-tw@nordson.com

**Nordson Test & Inspection Korea**  
ti-sales-korea@nordson.com



Specifications subject to change without prior notice.  
Copyright © Nordson 2024. Other products and company names mentioned are trademarks or trade names of their respective companies.

Nordson Test & Inspection products are patent protected and covered by the patent listed at [www.nordson.com](http://www.nordson.com).

BR-SQ3000-3DAOI 27/02/2024-V1